

OPTIONS**Power Type**

Battery

Body Type

Mid

Mounting

Deck

Power Supply

Battery (BAT)

Sensor Type

Infrared (IR)

Flow Rate

1.5 gpm (6 Lpm) (1.5GPM)

0.35 gpm (1 Lpm) (0.35GPM)

0.5 gpm (2 Lpm) (0.5GPM)

1.0 gpm (4 Lpm) (1.0GPM)

Spray Type

Aerated (AER)

Multi-Laminar (MLM)

Finish

Polished Chrome (CP)

Control Access

Above Deck

Mixer

Integrated Side Mixer (ISM)

Mixer Not Included

Special Features

IQ Click (IQ)

12s Timeout (12S)

Compliances & Certifications

ADA Compliant

ASME A112.18.1 Compliant

CEC Compliant

Proposition 65

TAS

UPC Certified

UPC Low Lead Compliant

cUPC Certified

cUPC Low Lead Compliant

NYC604.4




Image for a standard EAF-150 shown

DESCRIPTION

Optima® Battery-Powered Deck-Mounted Mid Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensors with Automatic Setup and Indicator Light
- Automatic Self-adapting Sensor Technology
- Low Battery Indicator
- Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 6 Volt Lithium 2CR5 Commercial Battery included
- Appropriate Mounting Hardware included
- Optional 24 Hour Sentinel Activation
- 3 year limited warranty

DOWNLOADS

- [EAF 100/150 Installation Instructions](#)
- [EAF 100/150 \(SP\) Installation Instructions](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [Optima Plus EAF 150 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com