

CONTEMPORARY DRINKING FOUNTAINS

GV Series

MODEL GVC59 BARRIER FREE. WALL MOUNTED DRINKING FOUNTAIN

STANDARD FEATURES

- Both Child and Adult Compliant (when properly installed)
- Resistant to sunlight, heat, moisture and wear
- 18 gage, 304 stainless steel bowl
- Reinforced concrete with aggregate finish
- Polished stainless steel, anti-rotation non-squirt bubbler
- 100 mesh inlet strainer
- P-trap, 1-1/4" O.D.
- Vandal resistant galvanized steel bottom plate and screws
- Mounting plate

SUGGESTED SPECIFICATIONS

Model GVC59 is a wall mounted, vandal resistant drinking fountain made from an 18 gage, 304 stainless steel bowl mounted into a brown concrete aggregate arm. Unit shall be activated by a front mounted selfclosing button, by using less than 5 pounds of force, which activates an internally mounted valve with an adjustable stream regulator controlling the water flow. Bubbler shall be polished stainless steel with a nonsquirt feature and operate on water pressure range of 20-105 psig. Fountain is certified to ANSI A117.1, Public Law 111-380 (NO-LEAD), CHSC 116875 and NSF/ANSI 61, Section 9. Fixture meets ADA, ADA Standing Person, and ADA Child requirements when mounted appropriately.



MODEL: (Must Specify)

GVC58 Tan Concrete Aggregate

GVC59 Brown Concrete Aggregate (Shown)

OPTIONS

(additional costs may be incurred)

Concealed support carrier □ -CSC -FRA1 Freeze resistant valve



















WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com



GVC59

04/20/18



CONTEMPORARY DRINKING FOUNTAINS

GV Series

MODEL GVC59 BARRIER FREE, 10" WALL MOUNTED DRINKING FOUNTAIN [254] 4" [102] 18" [457] Valve specifications: Minimum/Maximum Pressure 30 to 100 psi. 13" [330] [35] 6<u>1</u>" 3/8" NCT ◁ SUPPLY INLET [156] 1-1/4" [32] OD P-TRAP **PROVIDED** *28" [711]

GENERAL NOTES:

- 1. ALL DIMENSIONS ARE IN INCHES [MM].
- *2. DIMENSIONS SHOWN ARE FOR RECOMMENDED ADULT HEIGHT.
 ADJUST VERTICAL DIMENSIONS AS NECESSARY TO COMPLY WITH
 FEDERAL, STATE, & LOCAL CODES.
- 3. STOP VALVE NOT PROVIDED.

Murdock Mfg.™ warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Murdock™ is notified in writing within one year from date of shipment, F.O.B. Industry, California.

UMMARY AL FOR URING		_Quantity	All dimensions are subject to manufactures tolerance of plus or minus ½" nominal and subject to change without notice. Murdock
			assumes no responsibility for use of void or superseded data. Dimensions
PRC IUFA	Contact		may change with the addition of optional accessories. Murdock Mfg.™,
SELECTION S & APPROV MANUFACT	Signature (Approval for		Member of Morris Group International™. Please visit www.murdockmfg.com for most
S	Manufacturing)		current specifications.

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of MORRIS GROUP

GVC59 04/20/18