

OPTIONS**Flush Volume**

- 3.5 gpf (13.2 Lpf) (3.5)
- 1.6 gpf (6.0 Lpf) (1.6)
- 1.28 gpf (4.8 Lpf) (1.28)

Water Efficiency

- Water Saver
- Low Consumption
- High Efficiency

L Dimension

- 10 ¾" (273mm) (10-3/4-LDIM)
- 8 ¾" (222mm) (8-3/4-LDIM)
- 6 ¾" (171mm) (6-3/4-LDIM)
- 3 ¾" (95mm) (3-3/4-LDIM)
- 7 ¾" (197mm) (7-3/4-LDIM)
- 9 ¾" (248mm) (9-3/4-LDIM)
- 11 ¾" (298mm) (11-3/4-LDIM)
- 4 ¾" (121mm) (4-3/4-LDIM)
- 5 ¾" (146mm) (5-3/4-LDIM)
- 2 ¾" (70mm) (2-3/4-LDIM)

Wall Box

- Standard (not included, order separately)

Handle

- Metal Oscillating (J)

Push Button

- Metal Index (L)
- 3" Metal Oscillating (L3)

Control Stop

- 1" Straight (E)
- Ground Joint (GJ)
- Less (L/STOP)
- Adjustable Ground Joint (ADJ/GJ)
- Screwdriver (F)

Vacuum Breaker

- Less (XYV)

Outlet Tube


- Trap Primer (TP)

Bumper

- Double Wall (YI)

Special Features

- Whitworth Thread (WWT)

**DESCRIPTION**

Royal® Concealed Manual Water Closet Flushometer

FEATURES

- Flush volumes start as low as 1.28 gpf/4.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Concealed Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Compliances & Certifications

- BAA Compliant
- ADA Compliant
- UPC Certified
- cUPC Certified
- BREEAM Water Credit
- Green Globes Water Credit
- LEED V4 Water Efficiency Credit
- WaterSense Listed
- Satisfies LEED Credits
- cUPC Green Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.