



Penal-Ware® 1658 Series
18" Cafe-Lav/Hot Water Dispenser with Oval Bowl



1658-1-DMS-03

Fixture May Show Some Available Options

Please visit www.acorneng.com for most current specifications.

18" Cafe-Lav/Hot Water Dispenser with Oval Bowl

For use as a hot water dispenser to provide personnel with 190°F water for instant coffee, tea, hot chocolate, cereals, etc. The Cafe-Lav is provided complete with a 2/3 gallon hot water tank which will dispense up to 100 cups of 190°F water per hour.

Fixture is arranged to be installed on finished wall and serviced from an accessible pipe chase. Optional Wall Sleeve or Metal Template is recommended for all installations for required wall openings.

Cabinet is fabricated from 14 gage, type 304 stainless steel and is seamless welded construction with a satin finish. Cabinet interior is sound-deadened with fire-resistant material. There are no accessible voids or crevices where contraband can be concealed.

Oval Bowl is 14-3/4" x 9-1/2" x 5" deep. Standard elbow waste outlet is 1-1/2" O.D. plain end and extends 3" minimum beyond the rear of the fixture.

Optional Lavatory Valve is a single temperature, pneumatically operated, direct acting, pushbutton Air-Control valve, with connections to a chase mounted 190°F hot water unit that operates on 110 VAC. Lavatory spout is deck mounted. All electrical and plumbing connections by others. Valve and spout conform with lead free requirements for NSF61, Section 9 and CHSC 116875.

Regularly Furnished items include a fast drain, a hot water unit, a deck mounted spout, and mounting hardware for walls up to 8" thick.

GUIDE SPECIFICATION

Provide and install Acorn Penal-Ware 18" wide Cafe-Lav with Oval Bowl (specify model number and options). Fixture shall be fabricated from 14 gage, type 304 stainless steel. Construction shall be seamless welded and exposed surfaces shall have a satin finish. Cabinet bottom shall be enclosed and have no accessible voids or crevices where contraband can be concealed. Cabinet interior is sound-deadened with fire-resistant material. Fixture shall withstand loadings of 5,000 pounds without permanent damage. Fixture shall be furnished with necessary fasteners for proper installation. Hot water unit shall be provided for chase mounting. Valve and spout conform with lead free requirements for NSF61, Section 9 and CHSC 116875.

Penal-Ware® 1658: 18" Cafe-Lav/Hot Water Dispenser with Oval Bowl



WALL THICKNESS AND TYPE (Must Specify)

Thickness: _____ Type: Concrete Block Steel

MODEL AND OPTIONS SELECTION:

BASE MODEL NUMBER

1658 18" Cafe-Lav/Hot Water Dispenser I

FIXTURE MOUNTING AND WASTE (Must Specify)

-1 Off-Floor, Wall Outlet

SPOUT SELECTION (Must Specify)

-DMS Deck Mounted Spout

VALVE SELECTION (Must Specify)

Air-Control (Pneumatic)

-03 Single Temp, Non-Metering

Master-Trol® (Electronic)

-EVS1 Single Temp
 -EVSP1 Single Temp, Piezo Button

Master-Trol® PLUS (Electronic)

-MTP1 Single Temp
 -MTPP1 Single Temp, Piezo Button

Time-Trol® (Electronic)

-MVC1 Single Temp
 -MVC1-BAT Single Temp Battery Powered
 (Batteries Not Included)

Programmable (Electronic) w/9VDC Plug-In Transformer

-PPZ1 Single Temp Programmable Piezo Button

Valve By Others

-9 Punched for Valve by Others

VALVE OPTIONS

- BRS Brass Body Valve
- CI Cycle Interrupt for Time-Trol® Valves
- MA2 Manifolder, 2-Stack
- MA3 Manifolder, 3-Stack
- MA4 Manifolder, 4-Stack
- PBH Hemispherical Pushbutton
- PBP Pushrod Activated Pushbutton
- TF Transformer, 120VAC to 24VAC (-MVC option only)

CABINET OPTIONS

- FMT Fixture Mounted Trim
- IS Integral Shelf
- TG 12 Gage Cabinet
- TH Towel Hook Left Right


LAVATORY WASTE OPTIONS

- LW1 Thru-Wall Waste Extension with P-Trap
- LWE Lavy Waste Extension (3" Standard)
Specify Length Beyond Fixture: _____
- OF Lavatory Overflow
- PT P-Trap Waste

PRODUCT OPTIONS

- EG Enviro-Glaze, Specify Color: _____
- MT Metal Template (Only 1 Required Per Project)
- SW Wall Sleeve
- VAC AcornVac System

Please visit www.acorneng.com for most current specifications.



NOTES:

1. -03 Air-Control Valve
2. -DMS Deck Mounted Spout
3. Lavy Valve Pushbutton
4. Chase Mounted Hot Water Unit
5. Wall Mounted Hardware

1658-1-DMS-03

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

<p>Important: Installation instructions and current rough-in are furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of plus or minus 1/4" and change without notice. Acorn assumes no responsibility for use of void or superseded data. © Copyright 2009 Acorn Engineering Company</p>	
<p style="text-align: center;">Selection Summary</p> <p>Model No. & Option _____</p> <p>Quantity _____</p>	<p style="text-align: center;">Approved for Manufacturing</p> <p>Company _____ Title _____</p> <p>Signature _____ Date _____</p>