

OPTIONS

Power Supply

Plug Adapter (PLG) Hardwired Less Transformer (HLT)

Flow Rate

0.5 gpm (2 Lpm) (0.5GPM) 0.35 gpm (1 Lpm) (0.35GPM) 1.0 gpm (4 Lpm) (1.0GPM)

Spray Type

Aerated (AER) Multi-Laminar (MLM) Laminar (LAM)

Finish

Polished Chrome (CP)
Brushed Nickel (BN)
Brushed Stainless (SF)

Mixer

Mixer Not Included Integrated Side Mixer (ISM) Integrated Thermostatic Mixer

Special Features

IQ Click (IQ)
Carbon Offset (CO)
Less Logo (LL)
IC Click (IC)
Drain Pop Up (DPU)

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.



DESCRIPTION

Optima® Hardwired-Powered Deck-Mounted Mid Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensors with Automatic Setting Feature and Microprocessor
- Automatic Self-adapting Sensor Technology
- Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 6 Volt DC Plug-in Adapter (must be ordered separately for Less Adapter/Transformer (-LT) faucets)
- Appropriate Mounting Hardware included
- 3 year limited warranty

DOWNLOADS

- EAF 200/225/250/275 Installation Instructions
- EAF 200/225/250/275 (SP) Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 200 Repair and Maintenance Guide
- Additional Downloads

VIDEOS



Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com