



HYDRANTS

SafeWater™ Hydrant

MODEL M-NPL75

3/4" FREEZE RESISTANT POST HYDRANT
NON-POLLUTABLE, LEVER-OPERATED

STANDARD FEATURES

Model M-NPL75 delivers year-round service outside or in unheated buildings. The control valve is located below the frost line. Raising the lever opens the valve and lowering the lever shuts water off. The lever may be locked closed with a padlock (not included).


After use, water inside the supply column is stored in a reservoir below the frost line and is expelled thru the nozzle at the beginning of the next usage. This potable hydrant is protected against any surface or underground contamination. Recommended maximum operating pressure is 80 psi.

SUGGESTED SPECIFICATIONS

Hydrant shall be Murdock model M-NPL75. Lever-operated hydrant shall be ASSE 1057 certified as a potable hydrant. Hydrant shall not operate using venturi action. Unit shall be capable of year-round use in freezing weather. Hydrant shall have a flow rate of 2.5 gpm at 30 psi. Hydrant shall be serviceable from above grade.

Unit shall extend below grade level so that supply inlet, valve and reservoir are positioned below frost line. During shutoff, a piston shall draw water from the supply column into a reservoir. At the next usage, the piston shall expel the water in the reservoir thru the nozzle before fresh water flows. The water supply shall be protected against any surface or underground contamination.

Stock, top, base and handle shall be fabricated of heavy, one-piece iron castings finished with a heavy grade of oil-based green enamel. Solid brass castings in nozzle and inner supply assembly shall conform to ASTM standards B61 and B62. Lead-free castings shall be used in all waterways. Nozzle shall be threaded for 3/4" hose connection and shall include an ASSE 1011 self draining vacuum breaker.



Standard Model: M-NPL75

DEPTH OF BURY *(additional costs may be incurred)*

- | | |
|---|---|
| <input type="checkbox"/> 2 ft. (61 cm) | <input type="checkbox"/> 5 ft. (152.4 cm) |
| <input type="checkbox"/> 3 ft. (91.4 cm) | <input type="checkbox"/> 6 ft. (182.9 cm) |
| <input type="checkbox"/> 4 ft. (121.9 cm) | |

OPTIONS *(additional costs may be incurred)*

- VB ASSE 1052 vacuum breaker (for field testing)
- Plain end spout



Member of
U.S. Green
Building
Council



Recyclable
Product

Certified
by:



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov


MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA
Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of
MORRIS GROUP
INTERNATIONAL



HYDRANTS

SafeWater™ Hydrant MODEL M-NPL75 3/4" FREEZE RESISTANT POST HYDRANT NON-POLLUTABLE, LEVER-OPERATED



Murdock Mfg.™ warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Murdock™ is notified in writing within one year from date of shipment, F.O.B. Industry, California.

| | | | |
|---|--|----------------|--|
| SELECTION SUMMARY & APPROVAL FOR MANUFACTURING | Model Number & Options _____ | Quantity _____ | <p><i>All dimensions are subject to manufactures tolerance of plus or minus 1/2" nominal and subject to change without notice. Murdock assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock Mfg.™, Member of Morris Group International™. Please visit www.murdockmfg.com for most current specifications.</i></p> |
| | Company _____ | | |
| | Contact _____ | Title _____ | |
| | Signature (Approval for Manufacturing) _____ | Date _____ | |

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA
Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of MORRIS GROUP INTERNATIONAL